

# Fluid Data Specifications

<b>Model</b>	Supra	<b>Year</b>	1992
--------------	-------	-------------	------

<b>Model</b>	Supra
<b>Years Applied</b>	1992
<b>Engine</b>	7M-GTE , 7M-GE
<b>Transmission</b>	

### 7M-GTE

	Capacity	Type
	L (US.qt , imp.qt.)	
<b>A/C Refrigerant</b>	600 ~ 700g ( 1.3 ~ 1.5 lb. )	R12 use R134a
<b>Air condition Oil - Condenser</b>	40 ~ 50cc ( 1.4 ~ 1.7 fl.oz. )	ND-Oil 6 use 8 , Suniso No.5GS (see TSB )
<b>Air condition Oil - Receiver Drier</b>	20cc ( 0.7 fl.oz. )	"
<b>Air condition Oil - Evaporator</b>	40 ~ 50cc ( 1.4 ~ 1.7 fl.oz. )	"
<b>Air condition Oil - Pipes ( 3ft. or longer )</b>	5cc ( 0.6 fl.oz. )	"
-		
<b>Brakes</b>	-	SAE J1703 DOT3
<b>Clutch</b>	-	SAE J1703 DOT3
<b>Differential Oil</b>	1.3L ( 1.4 , 1.1 )	API GL-5 Above -18°C (0°F) SAE 90 Below -18°C (0°F) SAE 80W-90 or 80W
-		

### Engine Oil

<b>Engine Oil Dry Fill</b>	5.4L ( 5.7 , 4.8 )	SG
<b>Engine Oil w/Filter Change (Drain&amp;Refill)</b>	4.7L ( 5.0 , 4.1 )	SG
<b>Engine Oil w/oFilter Change (Drain&amp;Refill)</b>	4.4L ( 4.7 , 3.9 )	SG
-		
<b>Engine Cooling System w/ M/T</b>	8.2L ( 8.7 , 7.2 )	Ethylene glycol base ( no alcohol )
<b>Engine Cooling System w/ A/T</b>	8.1L ( 8.6 , 7.1 )	Ethylene glycol base ( no alcohol )
-		
<b>Fuel Tank</b>	70L ( 18.5 gal. , 15.4 imp.gal. )	Unleaded OR87 ( RON 91 ) or higher
-		
<b>Power Steering</b>	1,000cc ( 61.0 cu.in )	ATF Dexron II or III
-		

### Transmission fluid

<b>Automatic Transmission (Dry)</b>	7.2L ( 7.6 , 6.3 )	ATF Dexron II or III (see TSB )
<b>Automatic Transmission (Drain&amp;Refill)</b>	1.6L ( 1.7 , 1.4 )	ATF Dexron II or III (see TSB )
-		
<b>Manual Transmission - R154</b>	3.0L ( 3.2 , 2.6 )	API GL-4 or GL-5 SAE 75W-90 or 80W-90

### 7M-GE

	Capacity	Type
	L (US.qt , imp.qt.)	
<b>A/C Refrigerant</b>	600 ~ 700g ( 1.3 ~ 1.5 lb. )	R12 use R134a

<b>Air condition Oil - Condenser</b>	40 ~ 50cc ( 1.4 ~ 1.7 fl.oz. )	Densooil 6 use 8 , Suniso No.5GS (see TSB )
<b>Air condition Oil - Receiver Drier</b>	20cc ( 0.7 fl.oz. )	"
<b>Air condition Oil - Evaporator</b>	40 ~ 50cc ( 1.4 ~ 1.7 fl.oz. )	"
<b>Air condition Oil - Pipes ( 3ft. or longer )</b>	5cc ( 0.6 fl.oz. )	"
-		
<b>Brakes</b>	-	SAE J1703 DOT3
<b>Clutch</b>	-	SAE J1703 DOT3
<b>Differential Oil</b>	1.3L ( 1.4 , 1.1 )	API GL-5 Above -18°C (0°F) SAE 90 Below -18°C (0°F) SAE 80W-90 or 80W
-		
<b>Engine Oil</b>		
<b>Engine Oil Dry Fill</b>	4.9L ( 5.2 , 4.3 )	SG
<b>Engine Oil w/Filter Change (Drain&amp;Refill)</b>	4.4L ( 4.7 , 3.9 )	SG
<b>Engine Oil w/oFilter Change (Drain&amp;Refill)</b>	4.1L ( 4.3 , 3.6 )	SG
-		
<b>Engine Cooling System w/ M/T</b>	8.1L ( 8.6 , 7.1 )	Ethylene glycol base ( no alcohol )
<b>Engine Cooling System w/ A/T</b>	8.0L ( 8.5 , 7.0 )	Ethylene glycol base ( no alcohol )
-		
<b>Fuel Tank</b>	70L ( 18.5 , 15.4 )	Unleaded OR87 ( RON 91) or higher
-		
<b>Power Steering</b>	1,000cc ( 61.0 cu in. )	ATF Dexron II or III
-		
<b>Transmission fluid</b>		
<b>Automatic Transmission (Dry)</b>	7.2L ( 7.6 , 6.3 )	ATF Dexron II or III (see TSB )
<b>Automatic Transmission (Drain&amp;Refill)</b>	1.6L ( 1.7 , 1.4 )	ATF Dexron II or III (see TSB )
-		
<b>Manual Transmission - W58</b>	2.5L ( 2.6 , 2.2 )	API GL-4 or GL-5 SAE 75W-90 or 80W-90